

# AMERICAN ONSITE PRODUCTS

## BIOLINE FITTINGS



**TLCOUP**  
Insert Coupling



**TLELL**  
Insert Elbow



**TLTEE**  
Insert Tee



**TLCROS**  
Insert Cross



**TL050MA**  
1/2" Male Adapter



**TL075MA**  
3/4" Male Adapter



**TL075FTEE**  
Combination Tee  
Ins x Ins x 3/4" FPT



**TL2W075MA**  
2-Way Insert  
3/4" MPT x Insert



**TLIAPE-B**  
Insert Adapter for 1" or  
Larger PE (Requires 11mm  
or 7/16" drill or punch)



**TLIAPVC-B**  
Insert Adapter with Grommet  
1 1/2" or larger PVC Pipe



**TDBIT16.5**  
Drill Bit for TLIAPVC  
Fitting (16.5mm or 21/32")



**TLDPLUG**  
Dripper Plug Ring to Close Off  
Individual Dripper



**TLFIG8**  
Figure 8 Line End



**TLS6**  
6" Soil Staple



**TLSOV**  
Shut-Off Valve  
Ins x Ins



**TLCV**  
Inline Check Valve

- Flow Range: 0.9 to 4.4 GPM
- Opening Pressure: 7.1 psi
- Closing Pressure: 5.7 psi

### Fittings Definitions

**FPT** = Female Pipe Thread

**MPT** = Male Pipe Thread

**Ins x Ins** = Insert by Insert

### Applications

- Fits Bioline Dripperline

### Features/Benefits

- Barbed fittings for secure fit
- Easy installation without glue or tools
- Maximum recommended system pressure without clamps - 50 psi
- Allows for easy on-site inspection of proper fitting installation